

Model: iLED 10/12 BD 25 MUSHROOM

PRODUCT DESCRIPTION

The bollard luminaire is made of extruded aluminum and available in 6-12W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. It is ideal for driveways,pathways,gardens & etc.


Different fixture colours available on request.different heights available.

SPECIFICATION

Material Mounting Power	: Aluminium with powder coat and Milky/Frosted acrylic : Surface mount : 6-12 W
Voltage	: 90 – 270V AC,12/24 AC/DC
Power Factor	:>0.96
LED Colors	: White 6000-6400K
	Neutral White 4000-4500 K Warm
	White 2700-3000K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: D-200 X H-475 mm,Base Dia-115mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: >85
IP Rating	: IP 67
Led used	CREE 🚖
Dimmable (optional)	: CASAMBI, Colour tunable (2700K – 6000K), DALI,
	Edgo nulso/0/1-10\/ dimming control

Edge pulse/0/1-10V dimming control

ORDERING INFORMATION



The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in iLED Lighting Systems Pvt Ltd Chennai, Tamil Nadu, India 600096