



25°

## Ceiling Recess Mount Lights With Lens







**BEAM ANGLE** 

30°

10°

45°

5°

Model: iLED 3 RDL 03

## PRODUCT DESCRIPTION

The Ceiling recessed mount luminaire is made of Ventilated Aluminium with PMMA lens and available in 3 W. It is ideal for hotel, showroom, home, offices ,theaters etc. Different fixture colours available on request.

## **SPECIFICATION**

Material : Ventilated aluminum cooling with

PMMA lens

Mounting : Recess mount

Power : 3 W

Voltage : 12/24 V DC , 230 V AC LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W (lumen efficacy: 160 -180 lm)

Dimension : D-35 X H-50 mm

Cut out diameter : 27 mm
Driver : External

Operating Temp : -40°C ~ + 70°C

CRI : 85
IP Rating : IP 20
Led used : CREE €

Dimmable Interface : CASAMBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)

## **ORDERING INFORMATION**

03 WW NW **iLED** 3 **RDL** W Warm Neutral White **Brand** Rated Round Model No. White White name Power Down Light

The technical specifications may vary due to continuous improvement without prior notice.