


Bulbs



Model: iLED 5 CB 11, iLED 7 CB 12

PRODUCT DESCRIPTION


The bulb is made of ABS plastic and available in 5 W and 7 W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. It is ideal for hotel, restaurants, home, hospitals etc.

Different fixture colours available on request.

SPECIFICATION

Material Mounting	: Abs plastic : Retrofit: G24
Power	: 5 W, 7 W
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K
	Neutral White 4000-4500 K
	Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: D-37 X H-110 mm, D-37 X H-110 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 20
Led used	CREE 🚖
Dimmable Interface	CASAMBI, Colour tunable (2700 K – 6000 K), DALI,
	Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION



The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference