



25°

Ceiling Recess Mount Lights With Lens







BEAM ANGLE

30°

10°

45°

5°

Model: iLED 5 RDL 07

PRODUCT DESCRIPTION

The Ceiling recessed mount luminaire is made of aluminium with PMMA lens and available in 5 W. It is ideal for hotel, showroom, home, offices ,theaters etc.

Different fixture colours available on request.

SPECIFICATION

Material : Ventilated aluminum cooling with

PMMA lens & adjustable

Mounting : Recess mount

Power : 5 W

Voltage : 12/24 V DC , 230 V AC LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W (lumen efficacy: 160 -180 lm)

Dimension : D-110X H-62 mm

Cut out diameter : 86 mm
Driver : External

Operating Temp : -40°C ~ + 70°C

Dimmable Interface : CAS▲MBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

WW NW 07 **iLED** 5 **RDL** W Neutral White Warm Rated **Brand** Round Model No. White White Power name Down Light

The technical specifications may vary due to continuous improvement without prior notice.

^{*}Logos of products and companies are used for reference