


## ANTI STUMBLE light



**Model:** iLED 1.3 ASL 01

### PRODUCT DESCRIPTION

The anti stumble luminaire is made of plastic housing with PIR sensor and it is available in 1.3 W. Universal power supply/drivers with input range of 90 V to 270 V AC, 50/60 Hz and PF >0.96. It is ideal for bedroom, staircase, door key hole IDENTIFICATION, passage, corridor, toilet etc. *Different fixture colours available on request.*

### SPECIFICATION

Material	: Plastic housing with PIR sensor
Mounting	: Surface mount
Power	: 1.3 W
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 70-90 lm
Dimension	: L-80 X W-46 H-30 mm
Box Dimension	: 90 X 50 X 40 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 20
Led used	: <b>CREE</b> ⇄
Dimmable Interface	: <b>CASAMBI</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

### ORDERING INFORMATION

<b>iLED</b>	<b>1.3</b>	<b>ASL</b>	<b>01</b>	<b>W</b>	<b>WW</b>
Brand name	Rated Power	Anti Stumble light	Model No.	White	Warm White

The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference

[www.iled.in](http://www.iled.in)

iLED Lighting Systems Pvt Ltd  
Chennai, Tamil Nadu, India 600096