


Outdoor COB Down Lights





Model: iLED 10 RDL NA COB IP67 01

PRODUCT DESCRIPTION

The Outdoor COB Down Lights are in the range of 10 W, 15 W, 20 W,30 W and 40 W. Universal power supply/drivers with input range of 90 V to 305 V AC, 50/60 Hz and PF >0.96. It is more for Outdoor & ideal for hotel, showroom, home, office, theatres, auditorium, etc. Different fixture colours available on request.

SPECIFICATION

Material : Ventilated aluminum cooling with

polished reflector & tempered glass

Lumen Efficacy : 160 – 180 lumens Mounting : Recess mount

Power : 10W

Voltage : 90 V to 305 V AC 50/60 Hz

Power Factor : >0.96

LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W Dimension : D-100 X H-90 mm

Cut-out Dia : 90 mm
Driver : Internal

Operating Temp : $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$

CRI : 85 IP Rating : IP 67

Angle :5°,10°,25°,30°,45°

Led used : CREE €

Dimmable Interface : CASAMBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)

5° 10° 25° 30° 45°

The technical specifications may vary due to continuous improvement without prior notice.



VARIANTS

MODEL	RATED POWER	DIMENSION	
iLED 15 RDL NA COB IP67 02	15 W	D-130 X H-95 mm	
iLED 20 RDL NA COB IP67 03	20 W	D-160 X H-110 mm H-116mm	
iLED 30 RDL NA COB IP67 04	30 W	D-190 X H-130 mm H-133mm	
iLED 40 RDL NA COB IP67 05	40 W	D-230 X H-140 mm	

MODEL	RATED POWER	CUT-OUT DIMENSION
iLED 15 RDL NA COB IP67 02	15 W	115mm
iLED 20 RDL NA COB IP67 03	20 W	140mm D-125
iLED 30 RDL NA COB IP67 04	30 W	175mm
iLED 40 RDL NA COB IP67 05	40 W	200mm

ORDERING INFORMATION

iLED	10	RDL	01	W	WW	NW
Brand name	Rated Power	Round down Light	Model No.	White	Warm White	Neutral White