


Surface/SUSPENDED Mount
Down Lights



Model: iLED 10 SM RDL 22 – FR SERIES

PRODUCT DESCRIPTION

This surface mount luminaire is in the range of 3 W, 6W, 7W, 8W and 10W. Universal power supply/drivers with input range of 90 V to 305 VAC 50/60 Hz and PF >0.95. The material used is **ventilated aluminum cooling with reflector or lens**. It is ideal for hotel, Office, showroom, corridors etc.

SPECIFICATION

Material	: Ventilated aluminum cooling with reflector or lens
Lumen Efficacy	: 160 – 180 lumens
Mounting	: Surface mount / Suspended
Power	: 10 W
Voltage	: 90 – 305 VAC 50/60 Hz
Power Factor	: >0.95
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W
Light angle	: 5°, 10°, 15°, 25°, 30°, 45° & 60°
Dimension	: D-55 X H-156 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: >85
IP Rating	: IP 67
Led used	: CREE ⇄
Dimmable Interface	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)