



25°

## Spots Lights & Retrofits







**BEAM ANGLE** 

10°

45°

5°

30°

Model: iLED 12 MR16 COB 08

## PRODUCT DESCRIPTION

The Spots Lights & Retrofits luminaires are in the range of 8 -12W. Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.95 are provided. The material used is Ventilated aluminum cooling with polished reflector. It is ideal for hotel, showroom, home, office, theatres, auditorium, etc.

Different fixture colours available on request.

## **SPECIFICATION**

Material : Ventilated aluminum cooling with polished

Reflector

Lumen Efficacy : 160 – 180 lumens

Mounting : Retrofit with external power supply

Power : 8 - 12 W

Voltage : 90 V to 305 V AC 50/60 Hz

Power Factor : >0.95

LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W Dimension : D-50 X H-85 mm

Driver : External

Operating Temp : -40°C ~ + 70°C

CRI : 85 IP Rating : IP 20

Angle :5°,10°,25°,30°,45°

Led used : CREE €

Dimmable Interface : CASAMBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)

## ORDERING INFORMATION

WW NW 12 80 W **iLED** MR White Warm Neutral Multi facated **Brand** Rated Model No. White White Reflector name Power

The technical specifications may vary due to continuous improvement without prior notice.

www.iled.in iLED Lighting Systems Pvt Ltd Chennai, Tamil Nadu, India 600096

<sup>\*</sup>Logos of products and companies are used for reference