



25°

Spots Lights & Retrofits







BEAM ANGLE

10°

45°

5°

30°

Model: iLED 12 MR16 COB 10

PRODUCT DESCRIPTION

The Spots Lights & Retrofits ANGLE ADJUSTABLE luminaires are in the range of 4 W, 5 W, 6 W,8 W, 12W. Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.95. The material used is Ventilated aluminum cooling with PMMA lens.It is ideal for hotel, showroom, home, office, theatres, auditorium, etc.

Different fixture colours available on request.

SPECIFICATION

Material : Ventilated aluminum cooling with PMMA

lens

Lumen Efficacy : 160 – 180 lumens

Mounting : Retrofit with external power supply

Power : 12 W

Voltage : 90 V to 305 V AC 50/60 Hz

Power Factor : >0.95

LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W Dimension : D-50 X H-105 mm

Driver : External

Operating Temp : -40°C ~ + 70°C

CRI : 85 IP Rating : IP 20

Angle :5°,10°,25°,30°,45° ADJUSTABLE

Led used : CREE €

Dimmable Interface : CASAMBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

iLED 12 MR 10

0 W WW

VW N\

NW

Brand Rated Multi facated Model No. White Warm Neutral name Power Reflector White White

The technical specifications may vary due to continuous improvement without prior notice.

www.iled.in iLED Lighting Systems Pvt Ltd Chennai, Tamil Nadu, India 600096

^{*}Logos of products and companies are used for reference