


Stage Light with DMX Controller



Model: iLED 120 TH 251-PAR CAN

PRODUCT DESCRIPTION

The stage luminaires is in the range of 120W. Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.95 . The material used is ABS engineering plastic with aluminum heat sink with polished reflector and tempered glass.It is ideal to wall wash buildings, clubs, hotels, stages, parks, plazas etc.

Different fixture colours available on request.

SPECIFICATION

| | |
|--------------------|---|
| Material | : ABS engineering plastic with aluminum heat sink with polished reflector and tempered glass |
| Lumen Efficacy | : 160 – 180 lumens |
| Mounting | : Surface mount using aluminium clamps adjustable |
| Power | : 120 W |
| Voltage | : 90 V to 305 V AC 50/60 Hz |
| Power Factor | : >0.95 |
| LED colors | : White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K RGB |
| Lumen Flux | : 120-140 lm/W |
| Dimension | : D-255 X H-405 mm |
| Driver | : Internal |
| Operating Temp | : -40°C ~ + 70°C |
| CRI | : 85 |
| IP Rating | : IP 20 |
| Led used | : CREE ⇄ |
| Dimmable Interface | : CAS ▲ AMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional) |

ORDERING INFORMATION

| | | | | | | | |
|------------|-------------|-------------|-----------|-------|------------|---------------|----------------------|
| iLED | 120 | TH | 02 | W | WW | NW | RGB |
| Brand name | Rated Power | Stage Light | Model No. | White | Warm White | Neutral White | Red Green Blue |

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096