



Inwall Light indoor



Model: iLED 3/5 IWL CED 05

PRODUCT DESCRIPTION

This recessed mount luminaires is in the range of 3 W and 5 W. Universal power supply/drivers with input range of 24 V AC-DC and PF >0.95. The material used is Aluminum die cast with powder coating and lens. It is ideal for bedroom, passages, corridors etc. *Different fixture colours available on request.*

SPECIFICATION

Material	: Aluminum die cast with powder coating and lens
Lumen Efficacy	: 160 – 180 lumens
Mounting	: Inwall / 2-way switch box
Power	: 3 W/5W
Voltage	: 24 V AC-DC , 90 V to 305 V AC
Power Factor	: >0.95
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W
Dimension	: L-80 X W-80 X H-47 mm
Cut out dimension	: L-58/W-58/H-42mm
Driver	: external
Operating Temp	: -40°C ~ + 70°C
CRI	: >85
IP Rating	: IP 20 (OPTIONAL IP65)
Led used	: CREE ⇄
Dimmable Interface	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

iLED	3/5	IWL	05	W	WW	NW
Brand name	Rated Power	In wall light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096