



## Wall Lights Outdoor



**Model:** iLED 6 RPL 152 – 42

### PRODUCT DESCRIPTION

The wall luminaire is made of die cast aluminium. It is available in 6 W. Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.96. It is ideal for outdoor, passages, corridors etc.

*Different fixture colours available on request.*

### SPECIFICATION

Material	: Ventilated powder coated die cast aluminium with lens & tempered glass
Mounting	: Surface Mount
Power	: 6 W
Voltage	: 90 – 305 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: L-210 X W-45 X H-90 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 65
Led used	: <b>CREE</b> ⇄
Dimmable Interface	: <b>CASAMBI</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

### ORDERING INFORMATION

iLED	6	RPL	42	W	WW	NW
Brand name	Rated Power	Roof/Pillar Light	Model No.	White	Warm White	Neutral White