

Strip Lights



Model: iLED 6 STL 2835/60

PRODUCT DESCRIPTION

The strip lights are made of flexible copper available in the range of 6 W to 44 W. Universal power supply/drivers with input range of 24 V DC It is ideal for Cove lighting ,Profile lighting,signages, interior/ exterior lightings, accent lightings, under cabinet lightings, back lightings etc.
Different fixture colours available on request.

SPECIFICATION

Material	: Flexible Copper PCB with Silicon casing
Power	: 6 -44W
Voltage	: 24 V DC
Light Source	: 2835 / 5050 LED's
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K RGB, Other colors on request
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Width of the PCB	: 8 -30 mm (Depending on the wattages)
Driver	: External
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 33/67/68
Led used	: CREE ⇄
Dimmable Interface	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

VARIANTS

MODEL	RATED POWER	WIDTH OF THE PCB
iLED 12 STL 2835/120	12 W	8 -10 mm
iLED 16 STL 2835/120 OR ILED 5050/60	16 W	5-8 mm
iLED 20 STL 2835/168	20 W	10 mm
iLED 24 STL 2835/240	24 W	10 mm
iLED 44 STL 2835/360	44 W	30 mm

ORDERING INFORMATION

iLED	12	STL	01	W	WW	NW	RGB
Brand name	Rated Power	Strip Light	Model No.	White	Warm White	Neutral White	Red

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096