



## Wall Lights Outdoor



**Model:** iLED 6+6 U&D OD 29

### PRODUCT DESCRIPTION

The wall luminaire is made of die cast aluminium. It is available in 12 W with three lens provided with 2 W each and can emit light on one or two sides. Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.96. It is ideal for outdoor, garden and wall light. *Different fixture colours available on request.*

### SPECIFICATION

Material	: Ventilated powder coated die cast aluminum with V-shaped beam lens
Mounting	: Surface Mount
Power	: 12 W
Voltage	: 90 – 305 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: D-184 X W-45X H-95 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 65
Led used	: <b>CREE</b> ⇄
Dimmable Interface	: <b>CASAMBI</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

### ORDERING INFORMATION

iLED	6+6	U&D	OD	29	W	WW	NW
Brand name	Rated Power	Up Down	Outdoor	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference

[www.iled.in](http://www.iled.in)

iLED Lighting Systems Pvt Ltd  
Chennai, Tamil Nadu, India 600096