




Panel Down Lights Milky (Back Lit)







Model: iLED 7 SQ PDL 04

PRODUCT DESCRIPTION

The Back lit panel down luminaire is made of aluminium housing with PMMA high transitive milky diffuser and depending on the fixture size it is available in the range of 6 W to 24 W. Universal power supply/drivers with input range of 90 V to 270 V AC, 50/60 Hz and PF >0.96. It is ideal for hotel, showroom, home, office, theatres, auditorium, etc.

Different fixture colours available on request.

SPECIFICATION

Material : Powder coated aluminium housing with PMMA high transitive milky diffuser

Mounting : Recessed mount

Power : 7 W

Voltage : 90 – 270 V AC 50/60 Hz

Power Factor : >0.96

LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W (lumen efficacy: 160 -180 lm)

Dimension : L-110 X W-110 X H-30 mm

Cut-out dimension : L-93 X W-93 mm

Driver : External Operating Temp : $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$

Dimmable Interface : CAS▲MBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)




VARIANTS

MODEL	RATED POWER	DIMENSION
iLED 7 SQ PDL 04	7 W	L-110 X W-110 X H-30mm
iLED 16 SQ PDL 05	16 W	L-178 X W-178 X H-32mm
iLED 24 SQ PDL 06	24 W	L-220 X W-220 X H-35mm L-225XW-225X H-20mm
iLED 6 PDL 3IN 1 07	6 W	L-96 x W-96 x H-32mm(SQ)
iLED 12 PDL 3IN1 08	12 W	170 x 170 x 40mm(SQ)
iLED 18 PDL 3IN 1 09	18 W	L-220 x W-220 x H- 40mm(SQ)

MODEL	RATED POWER	CUT-OUT DIMENSION
iLED 7 SQ PDL 04	7 W	L-33X W-93mm
iLED 16 SQ PDL 05	16 W	L-152 X W-152mm
iLED 24 SQ PDL 06	24 W	L-195 X W-195mm L- 200XW-200mm
iLED 12 PDL 3IN 1 07	12 W	L-140x W-140 x H-35mm

ORDERING INFORMATION



The technical specifications may vary due to continuous improvement without prior notice.