



Garden Pole / Street Light



Model: iLED 80 PL 19



PRODUCT DESCRIPTION

The street light luminaire is made of die cast /Extrusion aluminium With PC Cover and it is available in the range of 30 W to 80 W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. It is ideal for pole lights / pathway lights. *Different fixture colours available on request.*

SPECIFICATION

Material	: Aluminum die casting graphite black finish with milky diffuser
Mounting	: Surface mount
Power	: 80 W
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: D-160 X H-4200 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 65
Led used	: CREE ⇄
Dimmable Interface	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

iLED	80	PL	19	W	WW	NW
Brand Name	Rated Power	Pole Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096