



Designer Gypsum Light-Trimless



**Model:** iLED GPL QJ SR2001-18

**PRODUCT DESCRIPTION**

The Designer gypsum recessed mount luminaire is made of gypsum/plaster available in the range of 5 W – 20 W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96 are provided. It is ideal for hotel, showroom, home, office, auditorium etc.

*Different fixture colours available on request.*

**SPECIFICATION**

Material	: Gypsum/ plaster milky diffuser & front removable
Mounting	: Recess mount
Power	: 5 W – 20 W
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: L-190 X W-190 X H-42 mm
Cut Out Dimension	: L-195 X W-195 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 20
Led used	: <b>CREE</b> ⇄
Dimmable Interface	: <b>CASAMBI</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

**ORDERING INFORMATION**

iLED		GPL	18	W	WW	NW
Brand name	Rated Power	Gypsum Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference