


Front Removable Fitting Frame (FR Series)





Model: iLED S-SCY105-Q-DEEP-FR SERIES

PRODUCT DESCRIPTION

The FR series Front removable recess mount Luminaire ideal, with out damaging the ceiling are made of aluminium and available in 10 W - 24 W.

Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. It is ideal for hotel, showroom, office, auditorium & etc.

Different fixture colours available on request.

SPECIFICATION

Type : Adjustable without light source

Material : Aluminum die casting

Mounting : Recess mount

Power : 10 W

Voltage : 90 – 270 V AC 50/60 Hz

Power Factor : >0.96 Holder : MR16

LED colors : White 6000-6400 K

Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W (lumen efficacy: 160 -180 lm)

Dimension : D-103 X H-70 mm

Cut out diameter : 93 mm

Driver : External

Operating Temp : -40°C ~ + 70°C

CRI : 85
IP Rating : IP 20
Led used : CREE

CRE

Dimmable Interface : CASAMBI, Colour tunable (2700 K – 6000 K), DALI,

Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

On WW NW **iLED** FR W request Neutral White Warm **Brand** Rated Front White White Removable name Power

The technical specifications may vary due to continuous improvement without prior notice.