

Table Lamps with Built in Battery Backup



Model: iLED Wall Mount LED Lamp 02

## **PRODUCT DESCRIPTION**


The wall mount luminaires are in the range of 5 W and 10 W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. Natural anodized aluminum+metal color gray tiltable and 360 degree rotatable on lamp holder with incorporated on/off switch. It is ideal for reading lamp. **SPECIFICATION** 

## Matarial

Material	: Natural anodized aluminum+metal color gray tiltable and 360 degree rotatable on lamp holder with incorporated on/off switch
Mounting	: Wall mount
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K
	Neutral White 4000-4500 K
	Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Finish	: Brushed nickel
Light Source	: LED Bulbs
Switch Type	: Knob Switch
Bulbs Base Type	: E27
Dimension	:D-140 X H-280mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 20
Led used	CREE 🚖
Dimmable (optional)	CASAMBI, Colour tunable (2700 K – 6000 K), DALI,
$\mathbf{\nabla}$ due invite a $(0/4, 40)$ / dimensional events	

Edge pulse/0/1-10 V dimming control

## ORDERING INFORMATION



The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference