



Bollards



Model: iLED 12/20 BD 670022

PRODUCT DESCRIPTION

The bollard luminaire is made of die cast aluminium and available in 12 W and 20 W. Universal power supply/drivers with input range of 90 V to 270 V AC, 50/60 Hz and PF >0.96. It is ideal for gate lights and pathway etc.

Different fixture colours available on request. Available at different heights 200/400/600/800 mm.

SPECIFICATION

Material	: Aluminum die casting matte finish with designed crystal clear diffuser
Mounting	: Surface mount
Power	: 12/20 W
Voltage	: 90 – 270 V AC, 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: D-108 X H-600 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 67
Led used	: CREE ⇄
Dimmable (optional)	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control

ORDERING INFORMATION

iLED	12/20	BD	670022	W	WW	NW
Brand name	Rated Power	Bollard	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai-600096, Tamil Nadu, India