


Solar Street Lights



Model: iLED 15 Solar Street Light System S01

PRODUCT DESCRIPTION

The solar street luminaires are in the range of 5W to 30w. Universal power supply/drivers with input range of 90 V to 305 V AC, 50/60 Hz and PF >0.95. Ventilated powder coated aluminum with clear lens. It is ideal for roads, pathway and garden.

Different fixture colours available on request.

SPECIFICATION

Solar Panel	: 30Wp X 1 No
Battery	: LITHIUM (ACCORDING TO CUSTOMER REQUIREMENTS)
Pole Height	: 3 meters
Panel Dimension	: 665 X 665 X 38 mm
Battery Dimension	: L-98 X W-98 X H-300 mm
Backup Time	: 20-24 hours
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 65/67
Dimmable	: DALI, Edge pulse/0/1-10 V dimming control

ORDERING INFORMATION

iLED	15	SSL	01	W	WW	NW
Brand name	Rated Power	Solar Street Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096