



## Burials & Pathway Lights




**Model:** iLED 3 PWL 67006-Four way

### PRODUCT DESCRIPTION

The outdoor burial mount luminaire is made of aluminium with PMMA lens and available in 3 W. It emits light in four directions. DC/Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. It is ideal for sign, facade area, accent and general lighting area etc. Different fixture colours available on request.

### SPECIFICATION

Material	: Ventilated aluminum die casting with PMMA lens
Mounting	: Outdoor burial mount
Power	: 3 W
Voltage	: 12 / 24 V AC/DC, 230V AC
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: D-50 X H-90 mm / W-85 X H-100 mm
Cut-out Dimension	: D-45 X H- 79 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 67
Led used	: <b>CREE</b> 
Dimmable Interface	: <b>CASAMBI</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

### ORDERING INFORMATION

iLED	3	PWL	67006	W	WW	NW
Brand name	Rated Power	Path Way Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference

[www.iled.in](http://www.iled.in)

iLED Lighting Systems Pvt Ltd  
Chennai-600096, Tamil Nadu, India