



Super Market Light



Model: iLED 36/40 TL T8 33004-TRI PROOF IP67

PRODUCT DESCRIPTION

The super market suspended/angular mount luminaires are in the range of 36 W, 40W. Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.95. The material used is Aluminum housing with PCB with polycarbonate milky cover. It is ideal for hotel, showroom, home, office, auditorium etc.

Different fixture colours available on request.

SPECIFICATION

Material	: Aluminum housing with PCB with polycarbonate milky cover
Lumen Efficacy	: 160 – 180 lumens
Mounting	: Batten type
Power	: 36/40W
Voltage	: 90 V to 305 V AC 50/60 Hz
Power Factor	: >0.95
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W
Dimension	: 4 feet
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 67
Led used	: CREE ⇄
Dimmable Interface	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

iLED	36/40	TL	33004	W	WW	NW
Brand name	Rated Power	Tube Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096