


Solar Street Lights



Model: iLED 60-70 Solar Street Light System S04

PRODUCT DESCRIPTION

The solar street luminaires are in the range of 5W to 10W. Universal power supply/drivers with input range of 90 V to 305 VAC 50/60 Hz and PF >0.95. Ventilated powder coated aluminum with clear lens. It is ideal for roads, pathway and garden.

Different fixture colours available on request.

SPECIFICATION

Solar Panel	: 100Wp X 2 No
Battery	: 12V 100 Ah X 2 No
Pole Height	: 6 meters
Panel Dimension	: 1325 X 665 X 35 mm
Battery Dimension	: L-142 X W-172 X H-378 mm
Backup Time	: 20-24 hours
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 65/67
Dimmable	: DALI, Edge pulse/0/1-10 V dimming control

ORDERING INFORMATION

iLED	60/70	SSL	04	W	WW	NW
Brand name	Rated Power	Solar Street Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai, Tamil Nadu, India 600096