



Mirror/Picture Lights




Model: iLED 8 ML 33001

PRODUCT DESCRIPTION

The Mirror/Picture luminaire are in the range of 8 W . Universal power supply/drivers with input range of 90 V to 305 V AC 50/60 Hz and PF >0.95. The material used is Ventilated aluminum with glass. It can be used above the mirror/picture.

Different fixture colours available on request.

SPECIFICATION

Material	: Ventilated aluminum with glass
Lumen Efficacy	: 160 – 180 lumens
Mounting	: Surface mount
Power	: 8W
Voltage	: 90 V to 305 V AC 50/60 Hz
Power Factor	: >0.95
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W
Dimension	: L-350 X W-83 X H-30mm L-337
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 20
Led used	: CREE 
Dimmable Interface	: CASAMBI , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

VARIANTS

MODEL	RATED POWER	DIMENSION
iLED 12 ML 02	12 W	L-485 X W-85 X H-30mm W-89

ORDERING INFORMATION

iLED	8	ML	33001	W	WW	NW
Brand name	Rated Power	Mirror Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

*Logos of products and companies are used for reference

www.iled.in

iLED Lighting Systems Pvt Ltd
Chennai - 600096, Tamil Nadu, India