


## Designer Gypsum Light-Trimless



**Model:** iLED GPL TD S3F1001-33003

### PRODUCT DESCRIPTION

The Designer gypsum recessed mount luminaire is made of gypsum/plaster available in the range of 5 W – 20 W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96 are provided. It is ideal for hotel, showroom, home, office, auditorium etc.

*Different fixture colours available on request.*

### SPECIFICATION

Material	: Gypsum/ plaster with front removable
Mounting	: Recess mount
Power	: 5 W – 20 W
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: L-200 X W-80 X H-55 mm
Cut Out Dimension	: L-205 X W-85 mm
Clip Movement	: 12-24 mm
Driver	: Internal
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 20
Led used	: <b>CREE</b> 
Dimmable Interface	: <b>CASambi</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

### ORDERING INFORMATION

iLED		GPL	33003	W	WW	NW
Brand name	Rated Power	Gypsum Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference

[www.iled.in](http://www.iled.in)

iLED Lighting Systems Pvt Ltd  
Chennai - 600096, Tamil Nadu, India