


## Garden Pole / Street Light



**Model:** iLED 30 PL 67005

### PRODUCT DESCRIPTION

The street light luminaire is made of die cast / Extrusion aluminium and it is available in the range of 30 W to 80 W. Universal power supply/drivers with input range of 90 V to 270 V AC 50/60 Hz and PF >0.96. It is ideal for pole lights / pathway lights.

*Different fixture colours available on request.*

### SPECIFICATION

Material	: Aluminum die casting graphite black finish with milky diffuser
Mounting	: Surface mount
Power	: 30 W
Voltage	: 90 – 270 V AC 50/60 Hz
Power Factor	: >0.96
LED colors	: White 6000-6400 K Neutral White 4000-4500 K Warm White 2700-3000 K
Lumen Flux	: 120-140 lm/W (lumen efficacy: 160 -180 lm)
Dimension	: 3.5 meters
Driver	: External
Operating Temp	: -40°C ~ + 70°C
CRI	: 85
IP Rating	: IP 65
Led used	: <b>CREE</b> ⇄
Dimmable Interface	: <b>CASAMBI</b> , Colour tunable (2700 K – 6000 K), DALI, Edge pulse/0/1-10 V dimming control (optional)

### ORDERING INFORMATION

iLED	30	PL	67005	W	WW	NW
Brand Name	Rated Power	Pole Light	Model No.	White	Warm White	Neutral White

The technical specifications may vary due to continuous improvement without prior notice.

\*Logos of products and companies are used for reference

[www.iled.in](http://www.iled.in)

iLED Lighting Systems Pvt Ltd  
Chennai-600096, Tamil Nadu, India