



In wall Lights Outdoor







Model: iLED 15 IWL 67006 -IP 65

PRODUCT DESCRIPTION

The recessed mount wall luminaire is made of aluminium die cast with powder coated and glass depending on the fixture size it is available in the range of 15 W. Universal power supply/drivers with input range of 90 V to 270 V AC, 50/60 Hz and PF > 0.96. It is ideal for outdoor, passages, corridors etc.

Different fixture colours available on request.

SPECIFICATION

: Aluminum die cast with powder coated glass Material

: In wall Mounting : 15 W Power

: 90 - 270 V AC, 50/60 Hz Voltage

Power Factor : >0.96

: White 6000-6400 K LED colors

> Neutral White 4000-4500 K Warm White 2700-3000 K

Lumen Flux : 120-140 lm/W (lumen efficacy: 160 -180 lm)

Dimension : L-230 X W-128 X H-90 mm Cut out dimension : L-220 X W-123 X H-83mm

Driver : Internal : -40°C ~ + 70°C **Operating Temp**

CRI : 85 IP Rating : IP 65 Led used CREE ÷

Dimmable Interface :CASAMBI, Colour tunable (2700 K – 6000 K),

DALI, Edge pulse/0/1-10 V dimming control (optional)

ORDERING INFORMATION

iLED

15

IWL

67006

W

WW

NW

Brand name Rated Power In Wall Light

Model No.

White

Warm White

Neutral White